

MMA-200**MMA-270****MMA-315****MMA-630****ZX7/ARC-400****ZX7/ARC-500**

Model / Parameters	MMA-200	MMA-270	MMA-315	MMA-630	ZX7/ARC-400	ZX7/ARC-500
Tegangan(V)	220V	220V	220V	220/380V	220/380V	220/380V
Frekuensi(HZ)	50/60	50/60	50/60	50/60	50/60	50/60
Daya(KW)	7.8	9.5	13	23	18.3	21
Daya tanpa beban(V)	62	54	69	69	69	69
Rentang Penyesuaian(A)	20-200	20-250	20-315	30-630	30-400	30-500
Durasi Pemuatan(%)	60	60	60	60	60	60
Kehilangan tanpa beban(W)	40	40	40	40	40	40
Efisiensi(%)	85	85	85	85	85	85
Faktor kekuatan	0.93	0.93	0.93	0.93	0.93	0.93
Tingkat isolasi	F	F	F	F	F	F
Peringkat	IP21	IP21	IP21	IP21	IP21	IP21

MIG-200**MIG-250****MIG-260****MIG-270****MIG/NBC-400****MIG/NBC-500**

Model / Parameters	MIG-200	MIG-250	MIG-260	MIG-270	MIG/NBC-400	MIG/NBC-500
Tegangan(V)	220V	220V	220V	220V	380V	380V
Frekuensi(HZ)	50/60	50/60	50/60	50/60	50/60	50/60
Daya(KW)	8	11.1	11.1	12.4	19.4	25
Daya tanpa beban(V)	36	50	50	56	70	79
Rentang Penyesuaian(A)	40-200	40-250	40-260	40-270	60-400	60-500
Durasi Pemuatan(%)	60	60	60	60	60	60
Kehilangan tanpa beban(W)	40	40	40	40	40	40
Efisiensi(%)	85	85	85	85	85	85
Faktor kekuatan	0.93	0.93	0.93	0.93	0.93	0.93
Tingkat isolasi	F	F	F	F	F	F
Peringkat	IP21	IP21	IP21	IP21	IP21	IP21

TIG-160A**TIG-200A****TIG-200AC/DC****TIG-250AC/DC****TIG-315A****TIG-315AC/DC**

Model / Parameters	TIG-160A	TIG-200A	TIG-200AC/DC	TIG-250AC/DC	TIG-315A	TIG-315AC/DC
Tegangan(V)	220V	220V	220V	220V	220/380V	380V
Frekuensi(HZ)	50-60	50-60	50-60	50-60	50-60	50-60
Daya(KW)	3.3	4.5	4.4	6.3	9.0	8.5
Daya tanpa beban(V)	58	58	56	56	54	70
Rentang Penyesuaian(A)	10-160	10-200	10-200	20-250	20-315	20-315
Durasi Pemuatan(%)	60	60	60	60	60	60
Kehilangan tanpa beban(W)	40	40	40	40	40	40
Efisiensi(%)	85	85	85	85	85	85
Faktor kekuatan	0.93	0.93	0.93	0.93	0.93	0.93
Tingkat isolasi	F	F	F	F	F	F
Peringkat	IP21	IP21	IP21	IP21	IP21	IP21

LGK/CUT-40**LGK/CUT-60****LGK/CUT-80****LGK/CUT-100****LGK/CUT-120****LGK/CUT-160**

Model / Parameters	LGK/CUT-40	LGK/CUT-60	LGK/CUT-80	LGK/CUT-100	LGK/CUT-120	LGK/CUT-160
Tegangan(V)	220V	380V	380V	380V	380V	380V
Frekuensi(HZ)	50-60	50-60	50-60	50-60	50-60	50-60
Daya(KW)	6.4	10	15	20	23.5	25.6
Daya tanpa beban(V)	230	240	270	270	270	320
Rentang Penyesuaian(A)	20-40	20-60	20-80	20-100	20-120	20-160
Durasi Pemuatan(%)	60	60	60	60	60	60
Kehilangan tanpa beban(W)	40	40	40	40	40	40
Efisiensi(%)	85	85	85	85	85	85
Faktor kekuatan	0.93	0.93	0.93	0.93	0.93	0.93
Tingkat isolasi	B	B	B	F	F	F
Peringkat	IP21	IP21	IP21	IP21	IP21	IP21

WS-315**WS-350****WS-500**

Model / Parameters	WS-315	WS-350	WS-500
Tegangan(V)	380V	380V	380V
Frekuensi(HZ)	50-60	50-60	50-60
Daya(KW)	22.6	24.6	30
Daya tanpa beban(V)	45	55	60
Rentang Penyesuaian(A)	20-315	20-350	20-500
Durasi Pemuatan(%)	60	60	60
Kehilangan tanpa beban(W)	60	60	100
Efisiensi(%)	85	85	85
Faktor kekuatan	0.93	0.93	0.93
Tingkat isolasi	F	F	F
Peringkat	IP21	IP21	IP21